

GENERAL SPECIFICATION TC-503 STORM

STANDARD FEATURES

- Lengths avail – 11'-5"; 9'-9"
- Side Heights Available – 40"; 50"
- Cu. Yd. Cap. - 11'-5"x50"=12.8; 11'5"x40"=10.2; 9'-9"x50"=11.3; 9'-9"x40"= 9.0
- Weight , 11'-5" – 1,913 lbs; 9'-9" - 1,655 lbs
- Type Hoist – double acting, NTEA CL C7 scissor with subframe, pendant control
- Dump Capacity – 11'-5" - 16,600 #; 9'-9" – 17,000#
- Floor – 2-3/8" high, extruded T6 alloy aluminum planks, 3/16" thick top surface, with stiffeners on 5" centers
- Body fully assembled from factory
- Longsills - T6 alloy 7" H-beam
- Rubrail 5-1/2" tall T6 alloy aluminum extrusion
- Full-height, solid rear barndoors
- All body & mounting hardware except shear plates stainless steel
- All doors may be easily removed
- F M V S S compliant markers with harness
- Tailgate chains have sleeve protectors

CONSTRUCTION

- Welded 5052 H32 sheet aluminum sides & stiffeners
- Side stiffeners on 20" centers
- Sides & stiffeners mat'l thickness .125"(1/8")
- All Corners thickness - .188"(3/16")
- All swinging doors have tie-backs

OPTIONS

- Side Access Door– 49" wide, passenger side, front
- 40" Cabguard with 6 tie-downs load capacity – 200 lbs
- Two way, top-drop Tailgate; single handle top-drop with 1" dia bushed top pins. Top-drop tailgate, 20" high & includes 30" perforated upper barndoors on 50" sides, 20" upper barndoors on 40" sides
- Bail-operated coal chute avail in two way tailgate
- Roll Tarp assembly of mesh Lumite®